Little GIANT.

GKPK-SC SERIES

APPLICATIONS

• For effective cleaning, deliming and descaling of coils (Coil cleaning chemicals not included)

FEATURES

- 5-gallon polyethylene tank
- Snap-on acrylic tank cover
- Tank baffle to reduce splash
- Includes 2-MD-SC magnetic drive pump with special volute for vertical installation (Pump only includes cCSAus mark)
- Stainless pump bracket
- 1/2" 0.D. intake and discharge
- 10' x 1/2' vinyl tubing
- Intermittent liquid temperature up to 150 °F
- Tubing clamps and adapters included
- Inlet filter screen
- 14.6' maximum head
- 6' power cord

SERIES SPECIFICATIONS

Item No.	Model	HP	Input	Цz		Watts	Discharge Size	Performance GPH (LPH) @ Head				Shut-Off Ft.	PSI	Cord	Weight (lbs)
item No.	model	HP	Voltage	HZ	(FLÀ)	(kW)	Discharge Size	1′	3'	6′	9′	Shut-Off FL	P31	Cord	weight (ibs)
562660	GKPK-SC	1/30	115	60	1.4	109	1/2" O.D.	510 (1933)	465 (1763)	410 (1554)	330 (1251)	14.6 (4.5 m)	6.3	6 (1.8 m)	11 (5 Kg)





GKPK-SC SERIES


REPLACEMENT PARTS & KITS


Item	Part Number					
Pump	580523					
Tank Cover	162125					
Baffle	162116					
Tubing 1/2" x 18"	944222					
Tubing 1/2" x 10"	944213					

ENGINEERING DATA










PERFORMANCE DATA



CONSTRUCTION

Tank	Polyethylene
Tank Cover	Acrylic
Pump Head	GF Polypropylene
Pump Shaft/Thrust Washers	Ceramic
Inlet/Outlet Tubing	Vinyl

